

## Ultrasonic Vapor Degreasers



### Features:

- *Various sizes & capacities*
- *Analog & digital controller options*
- *Stainless Steel 304 and 316L material*
- *Adjustable, thermostatically controlled heaters (ambient to 80°C)*
- *Plug-and-play, self-cleaning systems for pre- and post-removal of organic contaminants.*
- *Solvent-based systems use chemicals to force a more effective cleaning process for hard-to-remove contaminants such as heavy oils.*
- *Complete organic contaminants removal — Oils, greases, lubricants, rust inhibitors, etc.*
- *Pre-and post-cleaning — Ideal for all high-precision manufacturing industries*
- *Minimal solvent loss — Featuring a selective line of solvents that are EPA-approved and non-flammable*

### Technical Specifications

#### SOLVAC™ S1 - COMPACT ULTRASONIC VAPOR DEGREASER

Model	Tank Dimensions L x W x H	Basket Dimensions L x W x H	Voltage	System Solvent Capacity	Ultrasonic Frequency	Ultrasonic Power	Heat
S1-1010	10" x 10" x 9.5" 255mm x 255mm x 250mm	7.75" x 7.75" x 8.50" 196mm x 196mm x 215mm	208V-230V 50-60Hz	10.5 US gallons 39.75 litres	132kHz	375 watts	1200 watts
S1-1812	18.5" x 11.8" x 11.7" 470mm x 300mm x 297mm	15.25" x 9.25" x 8.50" 387mm x 234mm x 215mm	208V 3- 60Hz US 415V 3- 50Hz Europe	37 US gallons 140 litres	132kHz	1000 watts	4000 watts

#### SOLVAC™ S2 - TWIN SUMP, CO-SOLVENT ULTRASONIC VAPOR DEGREASER

Model	Tank Dimensions L x W x H	Basket Dimensions L x W x H	Voltage	System Solvent Capacity	Ultrasonic Frequency	Ultrasonic Power	Heat
S2-1812	19.7" x 15" x 14.4" 500mm x 388mm x 365mm	15.25" x 9.25" x 8.50" 387mm x 234mm x 215mm	208V 3- 60Hz US 415V 3- 50Hz	39 US gallons 150 litres	40 kHz wash sump 132 kHz rinse sump	750 watts	4000 watts